

**MODEL POLYTECHNIC KARUNAGAPPALLY**  
**NOTICE**

---

No.P/665/19/MPK

Dated: 22/10/2019

Sealed quotations are invited for the supply of the materials specified in the schedule attached below over leaf. The rates quoted should be for delivery of the articles at the places mentioned below the schedule. Necessary superscription, due date for the receipt of quotations, date up to which the rates will have to remain firm for acceptance and the name and address of officer to whom the quotation is to be sent are noted below. Any quotation received after the time fixed on the due date is liable to be rejected. The maximum period required for delivery of the articles should also be mentioned.

**THE ACCEPTANCE OF QUOTATIONS WILL BE SUBJECT TO THE FOLLOWING CONDITIONS:**

1. Acceptance of the quotation constitute a concluded contract. Nevertheless, The successful tendered must with in a fortnight / a month after the acceptance of his quotation furnish 5 percent amount of the contract as security deposited and execute an agreement at his own cost for the satisfactory fulfillment of the contract, if so required.
2. Withdrawal from the quotation after it is accepted or failure to supply within a specified time or according to specification will entail cancellations of the order and purchases being made at the officer's expense from elsewhere, any loss incurred thereby being payable by the defaulting party. In such an event the government reserve also the right to remove the defaulter's name from the list of government suppliers permanently or for a specified number of years
3. Samples, duly listed should be forwarded wherever possible under separate cover and the unapproved samples got back as early as possible by the offerers at their own expenses and the government will in no case be liable for any expense on account of the value of the samples or their transport charges etc. In case, the samples are sent by railway the railway receipt should be sent separately and not along with the quotation since the quotation will be opened only on the appointed day demurrage will have to be paid if the railway parcels are not cleared in time .The approved samples may or may not be returned at the discretion of the undersigned. Samples sent by v.p.p or freight to pay will not be accepted.
4. No representation for enhancement of price once accepted will be considered during the currency of the contract.
5. Any attempt of the part of tenders or their agents to influence the officers concerned in their favour by personal canvassing will disqualify the tenders.
6. If any license or permit is required tenderers must specify it in their quotation and also state the authority to whom application is to be made.
7. The quotation may be for the entire or part supplies. But the tenders should be prepared to carry out such portion of the supplies included in their quotation as may be allotted to them.
8. The prices quoted should be included of all taxes, duties, cesses, etc. which are or may become payable by the contractor under existing or future laws or rules of the country of origin / supply or delivery during the course of execution of the contract.
9. The tenders shall quote also the percentage of rebate (discount) offered by them in case the payment is made promptly within fifteen days / within one month of taking delivery of stores.
10. Special conditions, if any printed on the quotation sheets of the tenders or attached with the tenders will not be applicable to the contract unless they are expressly accepted in writing by the purchaser.

Due date and time for receipt of quotations : 12/11/2019, 12.00 Noon

Date and time for opening of quotations : 12/11/2019, 3.00pm

Date up to which the rates are to remain

firm the acceptance : One Month

Designation and address of officer to whom

The quotation is to be addressed : The Principal, Model Polytechnic College,  
Karunagappally. List attached in separate of the required items.

Sl.No	Name of item	Qty																								
1.	PA WALL SPEAKER 25W Input Power 25W RMS Power Taps on 100V 25/15/10/5W Impedence 400/670/1k/2kΩ Frequency Response 120-15,000Hz SPL at 1kHz (1W/1m) 94db	10 Nos.																								
2	<table border="1"> <thead> <tr> <th colspan="2">POWER AMPLIFIER 250W</th> </tr> </thead> <tbody> <tr> <td>Power Output</td> <td>: 300 WMax, 250W RMS at 10% THD, 220W Max, 160W RMS at 10% THD 220W RMS at 5% THD, 200W RMS at 2% THD</td> </tr> <tr> <td>Output Regulation</td> <td>S2 dB, no load to full load at 1kHz</td> </tr> <tr> <td>Input Channels</td> <td>6 × Mic 0.65m V/4.7kΩ, 2 × Aux 100m V/470 kΩ, 1 × Line 1V/50kΩ</td> </tr> <tr> <td>Frequency Response</td> <td>50-15,000Hz±3dB</td> </tr> <tr> <td>Signal to Noise Ratio</td> <td>60dB</td> </tr> <tr> <td>Tone controls</td> <td>Bass:±10dB at 100Hz, Treble±10dB at 10kHz</td> </tr> <tr> <td>Output</td> <td>Preamp 200mV/600Ω, Line 1V/1kΩ</td> </tr> <tr> <td>Speaker Output</td> <td>4Ω, 8Ω, 70V &amp; 100V</td> </tr> <tr> <td>Digital Player</td> <td>MP3 Player with USB. SD and MMC Card Reader</td> </tr> <tr> <td>Power supply</td> <td>AC:220-240V 50/60Hz DC:24V (2×12V Car Battery)</td> </tr> <tr> <td>Power consumption</td> <td>AC:460 VA DC : 6A</td> </tr> </tbody> </table>	POWER AMPLIFIER 250W		Power Output	: 300 WMax, 250W RMS at 10% THD, 220W Max, 160W RMS at 10% THD 220W RMS at 5% THD, 200W RMS at 2% THD	Output Regulation	S2 dB, no load to full load at 1kHz	Input Channels	6 × Mic 0.65m V/4.7kΩ, 2 × Aux 100m V/470 kΩ, 1 × Line 1V/50kΩ	Frequency Response	50-15,000Hz±3dB	Signal to Noise Ratio	60dB	Tone controls	Bass:±10dB at 100Hz, Treble±10dB at 10kHz	Output	Preamp 200mV/600Ω, Line 1V/1kΩ	Speaker Output	4Ω, 8Ω, 70V & 100V	Digital Player	MP3 Player with USB. SD and MMC Card Reader	Power supply	AC:220-240V 50/60Hz DC:24V (2×12V Car Battery)	Power consumption	AC:460 VA DC : 6A	1 No.
POWER AMPLIFIER 250W																										
Power Output	: 300 WMax, 250W RMS at 10% THD, 220W Max, 160W RMS at 10% THD 220W RMS at 5% THD, 200W RMS at 2% THD																									
Output Regulation	S2 dB, no load to full load at 1kHz																									
Input Channels	6 × Mic 0.65m V/4.7kΩ, 2 × Aux 100m V/470 kΩ, 1 × Line 1V/50kΩ																									
Frequency Response	50-15,000Hz±3dB																									
Signal to Noise Ratio	60dB																									
Tone controls	Bass:±10dB at 100Hz, Treble±10dB at 10kHz																									
Output	Preamp 200mV/600Ω, Line 1V/1kΩ																									
Speaker Output	4Ω, 8Ω, 70V & 100V																									
Digital Player	MP3 Player with USB. SD and MMC Card Reader																									
Power supply	AC:220-240V 50/60Hz DC:24V (2×12V Car Battery)																									
Power consumption	AC:460 VA DC : 6A																									
3	<table border="1"> <thead> <tr> <th colspan="2">16 Channel Zone Selector</th> </tr> </thead> <tbody> <tr> <td>Input</td> <td>: 1 × 100 V (nominal)</td> </tr> <tr> <td>Outputs</td> <td>: 16 × 100V (nominal)</td> </tr> <tr> <td>Switches</td> <td>: 16 Zone Selector switches, plus ALL CALL, Power On/OFF</td> </tr> <tr> <td>Power Supply</td> <td>: AC 220-240V, 50/60Hz ; DC 24V (2 × 12V Car Battery)</td> </tr> </tbody> </table>	16 Channel Zone Selector		Input	: 1 × 100 V (nominal)	Outputs	: 16 × 100V (nominal)	Switches	: 16 Zone Selector switches, plus ALL CALL, Power On/OFF	Power Supply	: AC 220-240V, 50/60Hz ; DC 24V (2 × 12V Car Battery)	1 No.														
16 Channel Zone Selector																										
Input	: 1 × 100 V (nominal)																									
Outputs	: 16 × 100V (nominal)																									
Switches	: 16 Zone Selector switches, plus ALL CALL, Power On/OFF																									
Power Supply	: AC 220-240V, 50/60Hz ; DC 24V (2 × 12V Car Battery)																									

4	<p style="text-align: center;"><b>WIRELESS DESKTOP MICROPHONE</b></p> <p><b><u>MICROPHONE</u></b></p> <p>RF Output Power            10mW (Max.)  Modulation Mode            FM  Microphone Element        Condenser, Cardioid  Maximum Deviation        <math>\pm 18\text{kHz}</math>  Frequency Response        100Hz-12kHz  Power Requirement        2<math>\times</math>1.5V Pencil Cells  Current Consumption        &lt;40mA  Controls                        ON/OFF Switch  Indication                     Red Ring LED in the                                        Gooseneck</p> <p>Dimensions                  W145<math>\times</math>H50<math>\times</math>D155 mm  Weight                         0.66kg (without battery)</p> <p><b><u>RECEIVER</u></b></p> <p>Frequency Stability        <math>\pm 0.005\%</math>  Audio Output                0-50mV adjustable  S/N Ratio                     &gt; 90dB  Distortion                    &lt;0.5%  Antenna type                Telescopic 220V-240V AC                                        50Hz for AC  Power Requirement        adaptor (supplied                                        alongwith)  Controls                        Power Switch, Output                                        Volume Control Red LED                                        for Power ON, Green &amp; Red  Indication                    LEDs for Signal  Dimensions                 W152<math>\times</math>H40<math>\times</math>-                                        D110m  Weight                         0.20 Kg.</p> <p><b><u>ACCESSORIES</u></b></p> <p>1a-Mic Cable, 1A- Connection  Cable, 1<math>\times</math>AC Adaptor,  2<math>\times</math>1.5V AA)Cells</p>	<b>1 No.</b>

P R I N C I P A L

Place: Karunagappally

Date : 22/10/2019

